



1-132 Quarter-Turn Pr20.1 L18/40 for Padlock



Avantages

- For cutout 20.1.
- IP66 according to DIN EN 60529.
- RH / LH application
- Grounding by grounding nut.
- A pre-assembled quarter-turn can be installed in the cutout.

Materials

- **Wing knob:** zinc die, chrome plated or black
- **Housing:** zinc die, zinc plated
- **Grounding nut:** zinc die

Notes

(S) Door-thickness see table
Please configure the quarter-turn with a cam.
Padlock feature only if cam is at 90° to the wing knob.
1. seal



Quarter-Turn, zinc die, for padlock

	Part Number	Surface	Version	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	200-9365.00-00000	black	Smooth coating	18 mm	max. 8 mm	screw-on	1 pc.



Assembly options

- 200-0001.00-00000 **Assembling cam without o-ring**
- 200-0002.00-00000 **Assembling cam with o-ring**
- 200-0006.00-00000 **Assembling cam 90° to wing knob without o-ring**
- 200-0007.00-00000 **Assembling cam 90° to wing with o-ring**



Accessories

- b) 1-102 **Cams L35/45 Steel**
- 1-103 **Slide Shoe for Cams**
- b) 1-262 **Cams variable**
- 1-350 **Rod Latch for Quarter-Turns L18 Pr20.1 RS/FS**
- MLA 1-103 **MLA Door Contact**

